

Gasket Man cc

Data Specifications Sheet

Natural Rubber (GP45)

GP40 is a blend of natural & synthetic rubber.

Applications

GP40 is a general purpose rubber.

It is not recommended for use with oils or hydrocarbons. Poor petrochemical, UV and ozone resistance.

GP40 rubber is used for scraper blades, skirting rubber, curtains, etc.

it is used extremely as a gasket material for low pressure water applications.

Advantages

Versatile compound

High elasticity

Good memory

Abrasion resistant

Can be formulated to give many different characteristics

Relatively low cost.

Physical Properties / Technical Data

The information represents typical values which can vary according to the application. These values do not constitute a performance guarantee. Users should determine, prior to use, the suitability of this material for their particular application

Medium grade NR/SBR with good abrasion resistance

Shore Hardnes (A)	45 ±5
Specific Gravity	1.35
Tensile Strength	3 MPa
Elongation @ break %	300
Compression Set %	25.8
Temperature Range	-30°C- +80°C

Gasket man cc
Unit C3
Dekema Park
284a Dekema Road
Wadeville
1422

Tel: 011 865 4347
Fax: 086 670 6773
Cell: 082 925 1497

Should you require any more information
please contact us for support.
You can also mail us at:
amanda@gasketmanonline.co.za