



Gum Rubber is a soft long-wearing natural rubber sheet that comes mostly in its natural tan color

Applications

This product has excellent abrasion and tear resistance.

It is very resilient and provides superior cushioning capability.

Pure gum is not designed for outdoor or oil resistant applications.

Often used for sand/shot blast curtains due to its high abrasion resistance and resilience.

Advantages

Long service life.

Superior abrasion resistance.

High tensile allowing for excellent tear strength.

Non-Marking with great elongation characteristics

Physical Properties / Technical Data

The information represents typical values which can vary according to the application.

These values do not constitute a performance guarantee. Users should determine, prior to use, the suitability of this material for their particular application.

Hardness, Shore A Durometer	40±5
Tensile Strength	2300 PS
Elongation	650 %
Heat Resistance	100°C, 70hrs
Change in Hardness	3 Duro
Change in Tensile	-90 %
Change in Elongation	-60 %
Lowest Working Temp	-4 °C
Highest Working Temp	+70 °C

Gasket Man cc Unit C3 Dekema Park 284a Dekema Road Wadeville 1422

Tell: 011 865 4347 Fax: 086 670 6773 Cell: 082 925 1497 Should you require any more information please contact us for support.
You can also mail us at:
amanda@gasketmanonline.co.za